



(12) **United States Patent**
Padovani et al.

(10) **Patent No.:** **US 9,124,344 B2**
(45) **Date of Patent:** **Sep. 1, 2015**

(54) **PILOT REFERENCE TRANSMISSION FOR A WIRELESS COMMUNICATION SYSTEM**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventors: **Roberto Padovani**, San Diego, CA (US); **Peter John Black**, San Diego, CA (US); **Nagabhushana T. Sindhushayana**, San Diego, CA (US)

3,018,663 A 1/1962 Dunlop
3,534,264 A 10/1970 Blasbalg et al.
(Continued)

(73) Assignee: **QUALCOMM Incorporated**, San Diego, CA (US)

FOREIGN PATENT DOCUMENTS

BR 9607900 A 1/1998
BR 9607621 A 6/1998

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 409 days.

OTHER PUBLICATIONS

(21) Appl. No.: **12/874,156**

Hayes Microcomputer Products, Inc., Smartmodem 1200B Hardware Reference Manual, Norcross, GA, 1986.

(22) Filed: **Sep. 1, 2010**

(Continued)

(65) **Prior Publication Data**

US 2010/0323748 A1 Dec. 23, 2010

Related U.S. Application Data

Primary Examiner — Ronald B Abelson

(74) *Attorney, Agent, or Firm* — Dalei Dong

(60) Division of application No. 11/858,840, filed on Sep. 20, 2007, which is a continuation of application No. 09/702,142, filed on Oct. 30, 2000, now Pat. No. 7,289,473, which is a continuation-in-part of

(Continued)

(51) **Int. Cl.**
H04J 3/06 (2006.01)
H04J 3/00 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **H04B 7/2687** (2013.01); **H04B 1/707** (2013.01); **H04W 52/325** (2013.01); **H04B 2201/70701** (2013.01); **H04J 3/0644** (2013.01)

(58) **Field of Classification Search**
CPC H04J 3/0685; H04J 3/0664; H04J 3/0608; H04J 3/0605; H04J 3/0632; H04J 3/0682; H04J 3/0614; H04J 3/00; H04L 47/10

USPC 370/503, 509, 510, 516, 519, 520

See application file for complete search history.

(57) **ABSTRACT**

A pilot reference transmission scheme well suited for high data rate wireless communication systems is disclosed. To maximize the amount of interference from transmissions from neighboring transmission sources (e.g., access points or base stations) during the pilot interval, and hence minimize the amount of interference from non-transmitting sources during the data intervals, the pilot references are transmitted in bursts at predetermined time intervals, and the pilot bursts from the access points are synchronized. This results in maximum interference contributions from non-transmitting neighboring access points, facilitating reliable estimation of worst case carrier-to-interference (C/I), and further allows the receiving devices (e.g., access terminals) to easily recognize the bursts as pilot reference. In one embodiment, each access point transmits the pilot bursts at or near its maximum transmit power level and no user-specific data is transmitted during the pilot bursts.

22 Claims, 7 Drawing Sheets

